

PHASE | Anton Bauer: BATERIAS L Series

- NP-F774.....p. 2
- NP-F976.....p. 3
- Carregador Single.....p. 4



NP-F774

L-Series 7.2V battery

The Anton/Bauer NP-F774 is a 7.2V, 4400mAh (30Wh) Li-Ion battery that provides long, reliable run-times and powers most Sony “L” series type cameras. It is also great for powering 7.2V accessories, such as field monitors and on-camera lighting.

- 4400mAh (30Wh)
- Reliable and long-lasting batteries
- Excellent run-times
- Fast charging
- To be used with Sony cameras that need “L” Series type batteries
- Battery solution for the SmallHD DP7-PRO Sony-L series field monitors
- Battery solution for Litepanels and Manfrotto on-camera lighting: Lykos, Croma 2, Micropro 2 and Spectra 2



NP-F774

SKU: 8675-0110

- Maximum Output Voltage: 7.4V
- Mean Output Voltage: DC 7.2V
- Capacity: 4400 mAh / 30Wh
- Battery Type: Li-Ion
- Size: 2.78 x 1.50 x 1.56 in. (7.06 x 3.81 x 3.96 cm)
- Weight (Approx.): 7.2 oz. (204g)
- Warranty: One year or 500 cycles

NP-F976

L-Series 7.2V battery

The Anton/Bauer NP-F976 is a 7.2V, 6600mAh (47Wh) Li-Ion battery that provides long, reliable run-times and powers most Sony “L” series type cameras. It is also great for powering 7.2V accessories, such as field monitors and on-camera lighting.

- 6600mAh (47Wh)
- Reliable and long-lasting batteries
- Excellent run-times
- Fast charging
- To be used with Sony cameras that need “L” Series type batteries
- Battery solution for the SmallHD DP7-PRO Sony-L series field monitors
- Battery solution for Litepanels and Manfrotto on-camera lighting: Lykos, Croma 2, Micropro 2 and Spectra 2



NP-F976

SKU: 8675-0109

- Maximum Output Voltage: DC 8.4V
- Mean Output Voltage: DC 7.2V
- Capacity: 6600 mAh / 47Wh
- Battery Type: Li-Ion
- Size: 2.78 x 1.50 x 2.37 in.
(7.06 x 3.81 x 6.01 cm)
- Weight (Approx.): 9.6 oz. (272g)
- Warranty: One year or 500 cycles

SINGLE CHARGER

L-Series 7.2V battery charger

The Anton/Bauer L-Series Single Position Charger is designed for L-Series batteries. Includes a charge control switch to toggle between ECO (slower charging) and FULL (fast charging). Additionally, includes a 5V USB output port to charge another device simultaneously.

- Compact design
- Lightweight and durable
- Single position charger for Anton/Bauer L-Series batteries
- LED indicator
- Charge Control Switch: ECO setting for slower charging
- FULL setting for fast charging
- 5V USB output port to charge another device simultaneously



Single Position Charger

SKU: 8475-0131

- Input Power: 100-240 VAC, 50/60 Hz, 100 mA (MAX)
- Output Power: 4.2-8.4 VDC, 800 mA (max).
USB 2.0 port: 5.0 VDC, 1.0 A (max.)
- Charging Time: 2-6 hrs.
- Size: 2 x 1.3 x 3.5 in. (5.1 x 3.3 x 9 cm)
- Weight: 3.1 oz. (88 g)
- Warranty: One year or 2,000 cycles

NOSSAS REPRESENTADAS:

ANTON[®] BAUER

Ikegami[®]



VISLINK
News & Entertainment

 **Litepanels**[®]

 **autoscript**
a clearer picture

Vinten

veset[☁]

TVlogic

Telemetrics Inc.
Camera Control Systems

interra
systems

 **sencore.**
Where Content Meets Technology[™]

SILVUS
TECHNOLOGIES

Value Your Content
thinklogical.
Trust Our Proven Ingenuity

CueScript[™]
A WAY WITH WORDS...

Video **Clarity**

Tools for Video Analysis


Anywave Communication

 **ImmediaTV**


CRYSTAL[™]

AJA
AJA VIDEO SYSTEMS INC

 **PHABRIX**[®]
broadcast excellence

 **AVP**

 **NATCI**


NVERZION[®]

 **TBC**



PHASE Engenharia Ind. e Com. Ltda.

Av. Olegário Maciel 231, Lojas 101 a 105
Barra da Tijuca | Rio de Janeiro, RJ | CEP 22 621 200
Tel +55.21.2493.0125

Av. Ibirapuera 2.907, Conj. B306 & 7 - Ed. Conv. Corp. Plaza – Torre C
Indianópolis | São Paulo-SP | CEP 04029-200
Tel +55 11 3589-0125

phase@phase.com.br | www.phase.com.br